



Cisco

650-474 Exam

**PAISESE - Introducing Cisco Identity Services Engine for
System Engineer**

Thank you for Downloading 650-474 exam PDF Demo

You can Buy Latest 650-474 Full Version Download

<https://www.certkillers.net/Exam/650-474>

<https://www.certkillers.net>

Question: 1

Which statement about Cisco Identity Services Engine high availability is true?

- A. Monitoring nodes are deployed in an active/active mode. One node serves as primary. All logs are sent automatically to both HA monitoring nodes.
- B. Administration nodes are limited to two and are deployed in an active/standby mode.
- C. Secondary Administrative node automatically becomes primary in the event of primary node failure.
- D. Monitoring nodes are deployed in an active/standby mode. All logs sent to the primary are replicated to the secondary node.
- E. Users are served from the secondary Monitoring node only if the active Monitoring node fails.

Answer: D

Question: 2

Which types of design are required in the Cisco ISE ATP program?

- A. schematic and detailed
- B. preliminary and final
- C. high-level and low-level designs
- D. top down and bottom up

Answer: C

Question: 3

Each node can have a different persona and associated services with that persona. Which persona cannot run with other personas on the same Cisco Identity Services Engine node?

- A. Inline Policy Service
- B. Administration
- C. Monitoring
- D. Policy Service

Answer: A

Question: 4

Which external identity sources are not supported on Cisco ISE 1.0?

- A. Sun ONE LDAP Directory Server
- B. Microsoft Active Directory
- C. RSA Authentication Manager

D. Novell NDS

Answer: D

Question: 5

Which two roles can be deployed across more than two nodes in an instance? (Choose two.)

- A. Monitoring
- B. Administration
- C. Inline Posture
- D. Pokey Service

Answer: AB

Question: 6

Which RADIUS extension is required for posture and profiling support?

- A. ARAP
- B. VSA
- C. CoA
- D. EAPOL

Answer: C

Question: 7

Which methods can be used to create usernames?

- A. general or random
- B. RFC2381 or IEEE 1493
- C. Knopf or WS naming
- D. manual or Ruby

Answer: A

Question: 8

Which option is the default authentication priority on a Cisco switch?

- A. MAB, 802.1X, Web-Auth
- B. 802.1X, MAB, Web-Auth
- C. MAB Web-Auth, 802.1X
- D. 802.1X, Web-Auth, MAB

Answer: B

Question: 9

Which statement about Inline Posture node deployment support is true?

- A. The Inline Posture node is supported on VMware ESX 4.1 but not on earlier versions ESX.
- B. The Inline Posture node is supported on any VMware/ESX/ESXi virtual appliance.
- C. The Inline Posture node is supported on the 1121, 3315, 3355, and 3395 appliance.
- D. The Inline Posture node is supported only on the 3315, 3355, and 3395 appliances.

Answer: C

Question: 10

Which appliance supports Cisco ISE 1.0?

- A. ACS 1120 Appliance
- B. VMWare ESX 3.5
- C. NAC 3390 Appliance
- D. NAC 3355 Appliance

Answer: D

Question: 11

In the Cisco ISE ATP program, what must the sales team submit to begin the sales process?

- A. a new product-hold waiver
- B. high-level and low-level designs
- C. a preliminary design and a request for equipment release
- D. a high-level design and BoM

Answer: B

Question: 12

When determining the number of endpoints for a user base, what is a good ratio for a starting point?

- A. 1-to-1
- B. 2-to-1
- C. 3-to-1
- D. 5-to-1

Answer: C

Question: 13

In a distributed deployment when co-locating the Administrator and Monitoring nodes on one appliance what is the maximum number of supported Policy Service nodes?

- A. 5
- B. 10
- C. 3
- D. 1
- E. 40

Answer: A

Question: 14

By default, which traffic does an 802.1X-enabled switch allow before authentication?

- A. all traffic
- B. no traffic
- C. traffic permitted in the port dACL on Cisco ISE
- D. traffic permitted in the default ACL on the switch

Answer: D

Question: 15

Which two deployment methods are supported with Cisco ISE 1.0 with RADIUS NAC?
(Choose two.)

- A. Unified Wireless
- B. HREAP - Local Switched
- C. HREAP - Central Switched
- D. Autonomous

Answer: AC

Question: 16

Which function does the Cisco NAC Agent not perform?

- A. Windows updates
- B. launch remediation program
- C. antivirus or antispysware definition updates
- D. Macintosh updates

Answer: D

Question: 17

Which scenario does not support Cisco ISE guest services?

- A. wired NAD with local WebAuth
- B. wireless LAN controller with central WebAuth
- C. wireless LAN controller with local WebAuth
- D. wired NAD with central WebAuth

Answer: B

Question: 18

Which statement about Change of Authorization and Inline Posture node is not true?

- A. Inline Posture node supports Layer 3 mode (router mode).
- B. Inline Posture node supports Layer 2 mode (bridge mode).
- C. All Cisco devices support Change of Authorization.
- D. Inline Posture node is used to provide Change of Authorization functionality on devices that lack native Change of Authorization support

Answer: C

Question: 19

Which option does the Cisco ISE guest service not provide?

- A. support for local WebAuth and central WebAuth
- B. integrated authentication support for guest and nonguest accounts
- C. auto-population of login username for self-service registration
- D. email or SMS with credentials created by Admin registration

Answer: C

Question: 20

Which Cisco ISE node does not support automatic failover?

- A. Inline Posture node
- B. Monitoring node
- C. Policy Services node
- D. Admin node

Answer: D

Question: 21

What is the maximum number of endpoints supported on 3315/3355/3395 providing all Cisco BE services respectively?

- A. 5000/1000/50000
- B. 3000/6000/10000
- C. 2000/4000/8000
- D. 1000/2000/5000
- E. 4000/8000/15000

Answer: B

Question: 22

Which statement is true?

- A. A Cisco ISE Advanced license is perpetual in nature.
- B. A Cisco ISE Advanced license can be installed on top of a Base and/or Wireless license.
- C. A Cisco ISE Wireless license can be installed on top of a Base and/or Advanced license.
- D. A Cisco ISE Advanced license can be used without any Base licenses.

Answer: B

Question: 23

At which OSI layer does WebAuth operate?

- A. Layer 2
- B. Layer 1
- C. Layers 4 and 7 in combination
- D. Layer 3
- E. Layer 4

Answer: C

Question: 24

What is the maximum number of supported endpoints on an appliance in stand-alone mode?

- A. 5,000
- B. 7,500
- C. 10,000
- D. 2,000

Answer: D

Question: 25

Which Cisco ISE deployment models support profiling?

- A. Wireless WPA Enterprise TKIP SSIDs
- B. Inline Posture nodes
- C. Cisco Adaptive Security Appliance
- D. Wireless WPA2 Personal AES SSIDs

Answer: B

Question: 26

In which scenario does Cisco ISE allocate an Advanced license?

- A. guest services with dACL enforcement
- B. endpoint authorization using SGA enforcement
- C. dynamic device profiling
- D. high availability Administrator nodes

Answer: C

Question: 27

Which two configurations are acceptable for base and advanced licenses? (Choose two)

- A. no base licenses, 750 advanced licenses
- B. 1000 base license, 500 advanced licenses
- C. 1500 base license, no advanced license
- D. 250 base licenses, 500 advanced licenses

Answer: BC

Question: 28

Which existing platforms support data migration to Cisco ISE 1.0?

- A. NAC4.X
- B. ACS 4.X
- C. NAC 3.X
- D. ACS 5.X

Answer: A

Question: 29

What is the maximum number of support endpoints supported in a Cisco ISE deployment?

- A. 50 endpoints
- B. 100 K endpoints
- C. 80 K endpoints
- D. 200 K endpoints
- E. 1 Million endpoints

Answer: B

Question: 30

What is the maximum syslog rate for the monitoring node without any drop with appreciable latency?

- A. 500 messages/sec
- B. 1000 messages/sec
- C. 2000 messages/sec
- D. 5000 messages/sec

Answer: B

Thank You for trying 650-474 PDF Demo

To Buy Latest 650-474 Full Version Download visit link below

<https://www.certkillers.net/Exam/650-474>

Start Your 650-474 Preparation

[Limited Time Offer] Use Coupon “CKNET” for Further discount on your purchase. Test your 650-474 preparation with actual exam questions.

<https://www.certkillers.net>